


Product Datasheet

Characteristic

XZCP1865L5

pre-wired connectors XZ - straight female - 1/2"20 UNF - 3 pins - cable PUR 5m



Main

accessory / separate part category	cabling accessory
accessory / separate part type	pre-wired connectors
series name	general purpose

Complementary

electrical connection	straight female connector, connector type: 1/2"20 UNF 3 pins
cable connector fixing	screw-on
collar material	metal
status LED	without
cable length	16.4 ft (5 m)
cable outer diameter	0.2 in (5.2 mm)
cable composition	3 x 0.34 mm ²
wire insulation material	PUR
System Voltage	250 V AC 300 V DC
Line Rated Current	4 A
contact resistance	<= 5000 µOhm
insulating resistance	>= 1 GΩ
product weight	0.4 lb(US) (0.18 kg)

Environment

IP degree of protection	IP67
ambient air temperature for operation	-31...194 °F (-35...90 °C) (static) 23...194 °F (-5...90 °C) (flexing)
ambient air temperature for storage	-31...212 °F (-35...100 °C)

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0649 -

REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------