



## BTCGC250, Mechanical Ground Clamp for Cable Tray

By Burndy

Catalog # [BTCGC250](#)

TRAY CLAMP 250 KCMIL - 6, Material : Aluminum, Tin plated finish.

### Features

- Tin plated aluminum for durable, long lasting corrosion resistance
- cULus 467 Listed for Grounding and Bonding in US and Canada
- cULus 2703 Listed for solar PV applications in US and Canada
- Accommodates most popular styles of cable tray with inside or outside flange
- Quick and easy installation
- no drilling or special tools required
- Set screw bonds clamp to the cable tray while another set screw securely fastens the grounding conductor to the clamp providing vibration resistance and outstanding pull-out values
- Grounding green hardware as required in Section 8.4 of UL2703

### General

Catalog Number BTCGC250  
UPC 621945468818

### Dimensions

Dimensions 2.25 in x .88 in x 2.43 in  
Height 2.43 in



Length 2.25 in  
Width .88 in

### Conductor Related

Conductor - AL Str Size Range 250Kcmil - 6 AWG  
Conductor - Copper Str Size Range 250Kcmil - 6 AWG

### Certifications And Compliance

Buy American Compliant Contact Manufacturer  
Certification - CSA Approved No  
UL Listed Yes

### Logistics

Minimum Pack Quantity 1

### Product Assets

[Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)  
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Sales Drawings - 50072428](#)



A Hubbell brand