



Main

Range of Product	I-Line
Product or Component Type	Plug-in unit
Module type	H-Frame

Complementary

[Ue] rated operational voltage	600 V AC 50/60 Hz
Phase	3 phase
Busbar description	Ground
Fuse type	H
Breaking capacity code	J
Disconnecter device type	Thermal magnetic circuit breaker 90 A 25 kA 600 V Thermal magnetic circuit breaker 90 A 65 kA 480 V Thermal magnetic circuit breaker 90 A 100 kA 240 V
Level or class	Class 5600
Wiring configuration	3-wire

Environment

Product Certifications	UL[RETURN]CSA
------------------------	---------------

Ordering and shipping details

Category	20183-PFH /PHG/PHJ/ PHL C/B PLUGS
Discount Schedule	PE7
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	32.00 lb(US) (14.515 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------