



Main

| Product or component type | Section |
|---------------------------|---------|
|---------------------------|---------|

Complementary

| | |
|--------------------------------|---|
| Fixing mode | Plug-in |
| [Ue] rated operational voltage | 600 V AC 50/60 Hz 277/480 V AC 50/60 Hz |
| Network number of phases | 3 phases |
| Busbar description | Ground |
| Fuse type | H |
| Breaking capacity code | L |
| Disconnecter device type | Associated circuit breaker 70 A 125 kA 240 V Associated circuit breaker 70 A 100 kA 480 V Associated circuit breaker 70 A 50 kA 600 V |
| Level or class | Class 5600 |
| Wiring configuration | 4-wire |

Environment

| | |
|------------------------|-----------|
| Product certifications | CSA UL |
|------------------------|-----------|

Packing Units

| | |
|------------------|--------------------------|
| Package 1 Weight | 32.00 lb(US) (14.515 kg) |
|------------------|--------------------------|

Offer Sustainability

| | |
|-------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |

| | |
|----------------------------|---|
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
