



### Main

Range of Product	Modicon LMC078
Product or Component Type	Profibus DP communication module
Range Compatibility	Modicon LMC078
Product Compatibility	Motion controller

### Complementary

Physical interface	RS485
Method of access	Master/slave
Integrated connection type	Profibus DP - 1 female SUB-D 9 12 Mbit/s

### Environment

Standards	UL 508 EN/IEC 61131-2 zone B CSA C22.2 No 142
Product Certifications	cULus[RETURN]CSA[RETURN]CE
Marking	CE
Ambient Air Temperature for Operation	41...131 °F (5...55 °C)
Ambient Air Temperature for Storage	-13...158 °F (-25...70 °C)
Relative Humidity	5...95 % without condensation
IP degree of protection	IP20IEC 61131-2
Pollution degree	2
Operating altitude	0...6561.68 ft (0...2000 m)
Vibration resistance	10 m/s <sup>2</sup> direct mounting
Shock resistance	100 m/s <sup>2</sup>

### Ordering and shipping details

Category	18350-PACDRIVEM
Discount Schedule	PC52
GTIN	3606485306940
Returnability	No

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.46 in (3.700 cm)
Package 1 Width	3.27 in (8.300 cm)
Package 1 Length	4.41 in (11.200 cm)
Package 1 Weight	3.67 oz (104.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	12

---

Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	3.17 lb(US) (1.436 kg)

---

### Offer Sustainability

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

---