Catalog Number
Notes
Type

Contractor Select™

FMVCSLS Vanity LED

Contemporary Switchable Square Vanity



Provides an LED lighting platform to deliver general or task lighting for residential and light commercial applications. Light engine delivers long life and excellent color to ensure a quality, low-maintenance light installation. Ideal for use in bathrooms, lavatories, hallways, corridors, stairways, utility areas and more.

FEATURES:

- Available in 24" and 48"
- 24in produces 1550 lumens, standard input = 27 watts.
- 48in produces 2960 lumens, standard input = 36 watts.
- Fixture is rated to deliver L70 performance at 50,000 hours and operates at 120-277 volts.

Catalog Number	UPC	Description	Lumens	Input Watts	Voltage	Color Temperature	Pallet qty.
FMVCSLS 24IN MVOLT 30K35K40K 90CRI BN M6	191848792117	2' LED Vanity	1550	27W	MVOLT	3000K, 3500K, 4000K	108
FMVCSLS 48IN MVOLT 30K35K40K 90CRI BN M4	191848792179	4' LED Vanity	2960	36W	MVOLT	3000K, 3500K, 4000K	48

Specifications

INTENDED USE:

Provides an LED lighting platform to deliver general or task lighting for residential and light commercial applications. Light engine delivers long life and excellent color to ensure a quality, low-maintenance light installation. Ideal for use in bathrooms, lavatories, hallways, corridors, stairways, utility areas and more.

CONSTRUCTION:

The Contemporary Square Vanity is constructed of a polycarbonate diffuser with housings available in a brushed nickel finish. The included canopy/junction box cover is removable for a more low-profile look. The white diffuser provides even illumination and softens the appearance of the LEDs for improved aesthetics.

OPTICS:

The FMVCSLS Contemporary Square Vanity has an integrated switch to select 3000K, 3500K or 4000K color temperature at the time of installation.

2' delivers 1550 lumens, and 4' delivers 2960 lumens at 3000K CCT with 50,000 hours of life.

See table to the right for delivered lumens at the different CCT color switch settings.

Extruded polycarbonate diffuser is of highly transmissive material to minimize LED image and provides high angle brightness control.

ELECTRICAL:

Long-life LEDs, coupled with a multivolt and dual dimmable capable driver, provide extended service life. Standard input = 27 watts, (2'); 36 watts, (4'). Fixture is rated to deliver L70 performance at 50,000 hours and operates at 120-277 volts.

This fixture is dimmable by either triac or 0-10V dimming. Use with approved triac or 0-10v dimmer only.

LISTINGS:

UL Listed to US and Canadian safety standards. Listed for damp locations.

Complies with 2019 Title 24, Part 6, JA8 High Efficacy LED light source requirements.

WARRANTY:


5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

SPECIFICATIONS	2FT	4FT
Length:	21-7/16 (545)	45-1/16 (1145)
Weight:	2.15 (.98)	3.15 (1.43)
3000K Lumens (LPW)	1550 (87)	2960 (84)
3500K Lumens (LPW)	1725 (99)	3240 (94)
4000K Lumens (LPW)	1740 (96)	3200 (89)

All dimensions are inches (millimeters) unless otherwise indicated. Weights are pounds (kilograms).



© 2014-2025 Acuity Brands Lighting, Inc. All rights reserved. Rev. 09/10/25