



Main

Product or Component Type	Single Throw Safety Switch
Disconnecter device type	Fusible disconnect
Number of poles	3
Electrical Connection	Lugs
Series name	Heavy duty

Complementary

Line Rated Current	400 A
Device Composition	None
Device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
Motor power hp	100 Hp at 480 V AC 50-60 Hz for 2 phases motors 250 Hp at 480 V AC 50-60 Hz for 2 phases motors 125 Hp at 600 V AC 50-60 Hz for 2 phases motors 350 Hp at 600 V AC 50-60 Hz for 2 phases motors 50 Hp at 250 V DC 50 hp at 600 V DC
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Tightening torque	550 lbf.in (62.14 N.m) (AWG 1/0...750 kcmil)
Height	46.25 in (1174.75 mm)
Width	32.5 in (825.50 mm)
Depth	10.13 in (257.30 mm)

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 3R/12 galvanized steel

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	265.00 lb(US) (120.202 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product