

ZQV 4N/20**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The plug-in cross-connections feature easy handling and quick installation. This saves a great deal of time during installation in comparison with screwed solutions.

General ordering data

| | |
|------------|--|
| Version | Cross-connector (terminal), Plugged, orange, 32 A, Number of poles: 20, Pitch in mm (P): 6.00, Insulated: Yes, Width: 27.95 mm |
| Order No. | 2883800000 |
| Type | ZQV 4N/20 |
| GTIN (EAN) | 4064675848769 |
| Qty. | 20 pc(s). |

Creation date November 26, 2024 12:20:29 PM CET

Catalogue status 26.11.2024 / We reserve the right to make technical changes.

ZQV 4N/20**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|----------|-----------------|------------|
| Depth | 120.7 mm | Depth (inches) | 4.752 inch |
| Height | 2.8 mm | Height (inches) | 0.11 inch |
| Width | 27.95 mm | Width (inches) | 1.1 inch |
| Net weight | 0.78 g | | |

Temperatures

| | | | |
|----------------------------------|----------------|----------------------------------|-----------------|
| Storage temperature | -25 °C...55 °C | Operating temperature | -60 °C...130 °C |
| Continuous operating temp., min. | -60 °C | Continuous operating temp., max. | 130 °C |

Material data

| | | | |
|---------------------------|-------|--------|--------|
| Material | Wemid | Colour | orange |
| UL 94 flammability rating | V-0 | | |

Additional technical data

| | | | |
|--------------------------|---------|----------------|---------|
| Explosion-tested version | No | Type of fixing | Plugged |
| Type of mounting | Plugged | | |

Cross-connector

| | | | |
|---------------------------|------|------|------|
| Rated current, multi-pole | 32 A | Type | Plug |
|---------------------------|------|------|------|

Dimensions

| | |
|-----------------|------|
| Pitch in mm (P) | 6 mm |
|-----------------|------|

General

| | |
|-----------------|----|
| Number of poles | 20 |
|-----------------|----|

Rating data

| | | | |
|---------------|-------|---------------|------|
| Rated voltage | 400 V | Rated current | 32 A |
|---------------|-------|---------------|------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000489 | ETIM 7.0 | EC000489 |
| ETIM 8.0 | EC000489 | ETIM 9.0 | EC000489 |
| ECLASS 9.0 | 27-14-11-40 | ECLASS 9.1 | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |
| ECLASS 12.0 | 27-14-11-40 | ECLASS 13.0 | 27-25-03-03 |
| ECLASS 14.0 | 27-25-03-03 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Important note

| | |
|---------------------|---|
| Product information | Due to stability and temperature reasons it is only possible to break out 60% of contact elements. The usage of cross connectors reduces the rated voltage to 400V. The voltage reduced to 25V if cut cross connection with blank cut edges are used. |
|---------------------|---|

Creation date November 26, 2024 12:20:29 PM CET

Catalogue status 26.11.2024 / We reserve the right to make technical changes.

2

Data sheet

ZQV 4N/20

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

ROHS Conform

Downloads

Engineering Data [CAD data – STEP](#)
Catalogues [Catalogues in PDF-format](#)