



## Main

Product or Component Type	Circuit breaker
Range	PowerPact P
Current Sensor Rating Range	400 A
Rated Current	400 A
Breaking Capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
Trip Unit Technology	Electronic, ammeter, Micrologic 6.0 A, LSIG
AWG Gauge	AWG 3/0...500 kcmil aluminum/copper)3

## Complementary

Device Short Name	A
Certifications	CSA UL listed IEC
Rated operational Voltage	600 V AC
Module Type	P-Frame
Mounting Location	Busbar
Mounting Mode	I-Line
Poles Description	3P
Circuit Breaker Rating Code	J
Continuous Current Rating	100 %
Electrical Connection	I-Line connection line Lugs load
Tightening Torque	442.54 lbf.in (50 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) AWG 3/0...500 kcmil) 8.85...11.51 lbf.in (1.0...1.3 N.m)
Height	12.86 in (326.64 mm)
Width	8.27 in (210.06 mm)

---

Depth	8.05 in (204.47 mm)
-------	---------------------

---

### Packing Units

---

Package 1 Weight	32.00 lb(US) (14.515 kg)
------------------	--------------------------

---

### Offer Sustainability

---

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
PVC free	Yes

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---