

## PRJBX36IW



*Pan-Way®* Power Rated Surface Mount Outlet Boxes are UL 5A listed to 600V and CSA Certified to 300V. For use with LDP, LDS, and T-45. *Pan-Way®* Low Voltage Surface Mount Outlet Boxes are one and two-gang style boxes for low voltage and or fiber optic applications. JBX3510\*\*, JB1\*\*, and JB1D\*\* are supplied with adhesive backing. All surface mount outlet boxes are available in four colors, IW (Off White) with EI (Electric Ivory), IG (International Gray) or WH (White).

- JBP1FS and JBP2FS assemble without the use of screws for faster installation
- JBP1FS and JBP2FS are supplied with adhesive backing to speed installation
- JBP1FS and JBP2FS accept Pan-Way® Snap-on Faceplates for superior aesthetics

**All AW (Arctic White) and two and three meter products are only available outside of North America as a standard item. Contact customer service for minimum order quantities, stock and other color availability.**

***For actual product color please refer to the Surface Raceway Color Chart located in***

### ***selection guides.***

▪ Part Number	PRJBX36IW
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Single gang two-piece screw together round outlet box. Box accepts UL/CSA devices not to exceed 10 lbs per (5 lbs per CSA). For use with Pan-Way® PD3 or PD6 profile raceway. 5.48"D x 1.14"H (139.2mm x 29.0mm). Breakouts for 3/4" or 1" diameter conduit.
▪ Product Type	Power Rated
▪ Material	PVC
▪ Color	International White
▪ Height (In.)	1.14
▪ Height (mm)	29.0
▪ Length (In.)	5.51
▪ Length (mm)	140.0
▪ Width (In.)	3.28
▪ Width (mm)	83.3
▪ CE Compliant	No
▪ Pricing Description	Single Gang Power Rated Round Junction Box for PD3 / PD6 Raceway
▪ Type	Junction Box
▪ Min. Order UOM	PC
▪ Min. Order Qty.	1