

Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part category	Mounting and fixing accessories
Accessory / separate part type	Fixing column
Offer type	Without mirror
Product compatibility	XUSL.E...76 to XUSL.E...106 with 4 beams XUSL.E...76 to XUSL.E...106 with 3 beams
Accessory / separate part destination	Safety light curtain type 4 Safety light curtain type 2

Complementary

Ambient air temperature for operation	-22...131 °F (-30...55 °C) -22...131 °F (-30...55 °C)
Ambient air temperature for storage	-22...158 °F (-30...70 °C) -22...158 °F (-30...70 °C)
Column height	52.36 in (1330 mm)
Height protected	41.73 in (1060 mm)
Net weight	9.70 lb(US) (4.4 kg)

Packing Units


Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	13.23 lb(US) (6 kg)
Package 1 Height	5.71 in (14.5 cm)
Package 1 width	7.87 in (20 cm)
Package 1 Length	55.91 in (142 cm)

Offer Sustainability


Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Dimensions

With XUSZFB2



With XUSZFB1



Mounting and Clearance

