

NSPEC CAT 5E CMR (100 MHz)

Description	NSPEC Cat 5E offers unbeatable value, as this fully TIA/EIA 568-B.2-compliant cable comes at a very practical price. NSPEC Cat 5E uses countdown footage marking and comes in a durable box with special features for fast and effortless installation.
Conductor	Solid bare copper
Insulation	Thermoplastic
Jacket	Flame Retardant, Polyvinyl chloride (PVC)
Compliance	UL Verified, UL 444, UL Listed CMR (UL 1666), ISO/IEC 11801, ANSI/TIA/EIA 568-A, ANSI/TIA/EIA 568-B.2, ANIS/TIA 568-C.2, ANSI/ICEA S-90-661-2002, RoHS Compliant
Applications	10BASE-T through 1000BASE-T Ethernet ATM and token ring



Product Code	AWG Size	Pair Count	Nom Diameter in (mm)	Nom Impedance (ohms)	Nom Velocity of Prop. (%)	Approx Weight lbs/kft (kg/km)	Jacket Colour
375EU10	24	4	0.197(5.0)	100± 15	69	19.25(28)	White
375EU30	24	4	0.1975(5.0)	100± 15	69	19.25(28)	Green
375EU40	24	4	0.1975(5.0)	100± 15	69	19.25(28)	Blue
375EU50	24	4	0.1975(5.0)	100± 15	69	19.25(28)	Yellow

CAT5E_CM.R.pdf