

Product data sheet

Specifications



Power distribution block, Linergy, 1 pole, 2 line, 6 load, 350A Cu, 600V

9080LBC263206

Product availability: Stock - Normally stocked in distribution facility

Main

Range	9080LB
Product	Power Distribution Block
Current Rating	350 A copper
Short Circuit Current Rating	65 kA

Complementary

Voltage Rating	600 V AC/DC
Mounting Type	Surface mount
Number of poles	2
Terminals per Pole	2 load 6 line
Wire Size	Line 2, AWG 14...AWG 2/0, copper Load 6, AWG 14...AWG 4, copper
Electrical Connection	Tin plated copper lugs
SCCR	100 kA UL 508 A
Ambient Air Temperature for Operation	-40...302 °F (-40...150 °C)
Block Material	Phenolic: block
Terminal Tightening Torque	Line lug 40 lbf.in (4.5 N.m) AWG 8 copper Line lug 35 lbf.in (4.0 N.m) AWG 14...AWG 10 copper Line lug 120 lbf.in (13.6 N.m) AWG 6...AWG 2/0 copper Load lug 35 lbf.in (4.0 N.m) AWG 14...AWG 4 copper
Wire stripping length	Load: 0.38 in (9.65 mm) for top connection Load: 0.75 in (19.05 mm) for bottom connection Line: 0.75 in (19.05 mm)
Height	4 in (101.6 mm)
Width	3.47 in (88.14 mm)
Depth	2.61 in (66.29 mm)
End Barrier	9080LB32

Environment

Certifications	UL recognized E60616 CCN XCFR2 CE CSA file 70361 class 6228 01
----------------	--

Ordering and shipping details

Category	US10CP121711
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	0CP1
GTIN	785901157120
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.000 in (7.620 cm)
Package 1 Width	4.400 in (11.176 cm)
Package 1 Length	5.300 in (13.462 cm)
Package weight(Lbs)	20.800 oz (589.670 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	16
Package 2 Height	11.000 in (27.940 cm)
Package 2 Width	9.700 in (24.638 cm)
Package 2 Length	13.600 in (34.544 cm)
Package 2 Weight	22.320 lb(US) (10.124 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions

