



Main

Range	PowerLogic
Product name	CT
Product or Component Type	Current transformer
Secondary current	80 mA
Line Rated Current	600 A

Complementary

Current transformer type	Standard for cable
Current transformer ratio	600 A/80 mA
[Ui] Rated Insulation Voltage	600 V
Depth	0.45 in (11.5 mm)
Diameter	Inner 1.28 in (32.5 mm) Outer 2.26 in (57.3 mm)
Net Weight	3.00 lb(US) (1.36 kg)
[Uimp] rated impulse withstand voltage	10 kV

Environment

Product Certifications	CE
------------------------	----

Ordering and shipping details

Category	09795-POWERLOGIC CURRENT TRANSFORMERS
Discount Schedule	PL1
GTIN	785901754152
Returnability	No
Country of origin	CA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.35 in (8.5 cm)
Package 1 Width	3.54 in (9.0 cm)
Package 1 Length	4.53 in (11.5 cm)
Package 1 Weight	3.50 lb(US) (1.588 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.