

Product Datasheet

Characteristic

XZCP1340L10

pre-wired connectors XZ - elbowed
female - M12 - 3 pins - cable PUR 10m



Main

accessory / separate part category	cabling accessory
accessory / separate part type	pre-wired connectors
series name	general purpose

Complementary

electrical connection	M12, 3 pins elbowed female connector
cable connector fixing	screw-on
collar material	metal
status LED	2 PNP LEDs
cable length	32.81 ft (10 m)
cable outer diameter	0.2 in (5.2 mm)
cable composition	3 x 0.34 mm ²
wire insulation material	PUR
System Voltage	10...30 V DC
Line Rated Current	4 A
contact resistance	5000 µOhm
insulating resistance	1 GΩ

Environment

IP degree of protection	IP65 IP67 IP69K
product certifications	cULus
ambient air temperature for operation	-40...176 °F (-40...80 °C) (static) 23...176 °F (-5...80 °C) (flexing)
ambient air temperature for storage	-40...176 °F (-40...80 °C)

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity

REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available
