



Main

Product or Component Type	Industrial Control Transformer
Range of Product	EL

Complementary

Phase	1 phase
Rated power in VA	100 VA
Primary Voltage	550 V 575 V 600 V
Secondary Voltage	120 V 110 V 115 V
Temperature rise	55 °C
Electrical Connection	Screw clamp terminals
Connector type	Lead 2001.31 ft (610 m)

Environment

Product Certifications	CE[RETURN]CSA[RETURN]UL Listed
NEMA Degree of Protection	Not rated (open device)
Insulation temperature	221 °F (105 °C)

Ordering and shipping details

Category	16208-9070 9070 AP,E,G,H,SB, T, TF, (ALL)
Discount Schedule	CP8
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.50 in (8.89 cm)
Package 1 Width	3.88 in (9.855 cm)
Package 1 Length	4.00 in (10.16 cm)
Package 1 Weight	3.90 lb(US) (1.769 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------