



Main

Product or component type	Single Throw Safety Switch
Disconnecter device type	Non-fusible disconnect
Number of poles	4
Electrical connection	Lugs
Series name	Heavy duty

Complementary

Line Rated Current	600 A
Device composition	None
Device mounting	Surface
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 3/0...500 kcmil copper or aluminium
Maximum Horse Power Rating	200 Hp 240 V AC 50...60 Hz 3 phase NEC 430.52 400 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 500 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 50 Hp 250 V DC 50 hp at 600 V DC
Height	50.25 in (1276.35 mm)
Maximum Width	33.88 in (860.55 mm)
Depth	10.13 in (257.30 mm)
Tightening torque	375 lbf.in (42.37 N.m) AWG 3/0...500 kcmil

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 3R/12 galvanized steel

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product