



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

General

| | |
|-------------------------------------|-------------|
| Provided equipment | User Manual |
| Number of tare power | 1 W |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |
| UPS size | WS |

Physical

| | |
|---------------------|----------------------|
| Cable length | 5 ft (1.52 m) |
| Color | Black |
| Depth | 4.13 in (10.5 cm) |
| Height | 5.52 in (14.02 cm) |
| Mounting preference | No preference |
| Product Weight | 5.73 lb(US) (2.6 kg) |
| Mounting Mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | No |
| Width | 9.98 in (25.35 cm) |

Input

| | |
|---------------------------------|--------------------------------|
| Input Frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Plug standard | NEMA 5-15P |
| Efficiency at full load | 88...139 V |
| Maximum Input Current per Phase | 5 A |
| Switching current capacity | 7 A |
| Number of cables | 1 |
| Nominal Input Voltage | 120 V |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Output

| | |
|----------------------------------|------------------------------------|
| Kw Rating | 255 W |
| Max Configurable Power (Watts) | 255 W |
| Output Frequency (sync to mains) | 50/60 Hz +/- 3 Hz sync to mains |
| Topology | Standby |
| Waveform Type | Square wave |
| Nb of power socket outlets | 4 NEMA 5-15R 2 NEMA 5-15R surge |
| Curve equation | Efficiency |
| Curve fixed loss | 0.0114 |
| Curve load maximum | 100 % |
| Curve load minimum | 2 % |
| Curve proportional loss | 0 |
| Curve square loss | 0.0036 |
| Curve X-axis maximum | 100 % |
| Curve test cond ID | Curve fit of data US DOE Test |
| Curve X-axis minimum | 0 % |
| Curve X-axis title | Load |
| Curve X-axis units | Percentage |
| Curve Y-axis maximum | 100 % |
| Curve Y-axis minimum | 50 % |
| Curve Y-axis title | Efficiency |
| Curve Y-axis units | Percentage |
| Graph display | 1 |
| Graph start point | 10 |
| Output voltage | 120 V |
| Maximum configurable power in VA | 425 VA |
| Rated power in VA | 425 VA |
| Transfer Time | 6ms typical : 10ms maximum |

Conformance

| | |
|-----------------------------|--|
| Product Certifications | California (CEC) Battery Charger cTUVus |
| Standards | FCC Part 15 class B |
| Equipment protection policy | Lifetime : \$75000 |

Environmental

| | |
|---------------------------------------|----------------------------------|
| Ambient Air Temperature for Operation | 32...104 °F (0...40 °C) |
| Relative Humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -4...122 °F (-20...50 °C) |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |
| Acoustic level | 40 dBA |
| Show note OP temperature | No |

Batteries & Runtime

| | |
|------------------------------|-------------------|
| Battery Type | Lead-Acid battery |
| Included Battery Modules | 0 |
| Battery Slots Empty | 0 |
| Typical recharge time | 8 h |
| Liquid Electrolyte Value | 0 |
| Battery curve | C |
| Battery Charge Power (Watts) | 6 W rated |

| | |
|------------------------|--|
| Battery power in VAH | 47 VAh runtime |
| Battery life | 3...5 year(s) |
| Battery graph comments | This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load. |
| Extendable Run Time | 0 |

Communications & Management

| | |
|---------------|---|
| Control panel | LED Status display with On Line : On Battery |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm |

Surge Protection and Filtering

| | |
|---------------------|-------|
| Surge energy rating | 180 J |
|---------------------|-------|

Ordering and shipping details

| | |
|---------------------|--------------------|
| GTIN | 00731304329343 |
| Package weight(Lbs) | 6.61 lb(US) (3 kg) |

Packing Units

| | |
|------------------------------|------------------------|
| Package 1 Height | 8.66 in (22 cm) |
| Package 1 width | 12.40 in (31.5 cm) |
| Package 1 Length | 5.51 in (14 cm) |
| SCC14 | 10731304329340 |
| Number of Units in Package 2 | 2 |
| Package 2 Weight | 14.33 lb(US) (6.50 kg) |
| Package 2 Height | 12 in (304.80 mm) |
| Package 2 width | 13 in (330.20 mm) |
| Package 2 Length | 10 in (254.00 mm) |
| Number of Units in Package 3 | 96 |
| Package 3 Height | 49.61 in (126 cm) |
| Package 3 width | 39.37 in (100 cm) |
| Package 3 Length | 47.24 in (120 cm) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 3 years repair or replace |
|----------|---------------------------|