

# Eaton CSR6352

Catalog Number: CSR6352

Eaton Crouse-Hinds series Arktite CSR interlocked receptacle, 60A, Brass contacts, Fused, Style 2, 20 HP/40 HP, Krydon fiberglass-reinforced polyester, 1-1/4", 250-600 Vac

## General specifications

Product Name	Catalog Number
Eaton Crouse-Hinds series Arktite CSR interlocked receptacle	CSR6352
	UPC
	782274229836
Product Length/Depth	Product Height
8 in	19.26 in
Product Width	Product Weight
7.78 in	20.15 lb



## Certifications and compliances

### Area classification

Ordinary/Non-Hazardous Locations

### Standards type

NEC/CEC

### NEMA Rating

3

4

4X

12

### Ingress protection (IP) ratings

IP66

## Product specifications

### Amperage Rating

60A

### Trade size

1-1/4"

### Fusing

Fused

### Voltage rating

250-600 Vac

### Horsepower

20 hp/40 hp

### Grounding style

Style 2

### Material

Krydon fiberglass-reinforced polyester

### Contact material

Brass

## Resources

### Catalogs

[Arktite CSR Nonmetallic Interlock Receptacles catalog page](#)

### Certification reports

[Arktite CSR Nonmetallic Interlock Receptacles UL certification](#)

[Arktite CSR Nonmetallic Interlock Receptacles Canadian certification](#)

### Installation instructions

[IF 1439 - CSR 30A and 60A Interlocked Receptacle](#)

[IF 1334 - CSR Interlocked Receptacle](#)

[IF 1440 - CSR 30A and 60A Interlocked Receptacle with Bussmann Fuses](#)

### Specifications and datasheets

[Eaton Specification Sheet - CSR6352](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)