



Main

Range of Product	Lexium P, T
Product or Component Type	Delta 3 robot
Device short name	P4
Design	Standard

Complementary

Number of axis	3
Work envelope	0.00...47.24 In (0...1200 mm) diameter 0.00...16.73 in (0...425 mm) vertical
Repeat accuracy	0.1 mm
Permanent permissible load	33.07 lb(US) (15 kg)
Maximum actuation speed	32.81 ft/s (10 m/s)
Maximum acceleration	328.08 Ft/S ² (100 m/s ²) at 1 kg 246.06 ft/s ² (75 m/s ²) at 1.5 kg
Net Weight	253.53 lb(US) (115 kg)
Range Compatibility	Lexium 62 ILM motor

Environment

Environmental characteristic	Normal environment High pressure cleaner Dust pollution resistance
------------------------------	--

Ordering and shipping details

Category	18357-PACDRIVE ROBOTIC
Discount Schedule	PC52
GTIN	3606485307114
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	53.15 in (135.0 cm)
Package 1 Width	47.24 in (120.0 cm)
Package 1 Length	39.37 in (100.0 cm)
Package 1 Weight	286.60 lb(US) (130.0 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes