



Main

Range of Product	Modicon STB distributed I/O solution
Product or Component Type	Auxiliary power supply kit
Product Specific Application	Supply for logic of I/O module

Complementary

Kit composition	Terminal spring clamp connector STBXBA2100 base STBCPS2111 module Terminal screw type connector
[Us] rated supply voltage	24 V
Supply circuit type	DC
Supply voltage limits	19.2...30 V
Input current	400 mA
Output voltage	5.25 V +/- 0.21 % logic bus
Output voltage type	DC
Power supply output current	1.2 A
Electrical connection	2 pins for removable connector power supply
Marking	CE
Overvoltage category	II

Environment

Electromagnetic compatibility	Immunity to electromagnetic interference IEC 61131-2
Product Certifications	UL[RETURN]CSA[RETURN]FM Class 1 Division 2
Pollution degree	2 IEC 60664-1
Operating altitude	<= 6561.68 ft (2000 m)
IP degree of protection	IP20 conforming to IEC 61131-2 class 1
Ambient air temperature for operation	-13...158 °F (-25...70 °C) without derating)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % 140 °F (60 °C) without condensation
Vibration resistance	3 gn 58...150 Hz 35 x 7.5 mm symmetrical DIN rail 5 gn 58...150 Hz 35 x 15 mm symmetrical DIN rail +/-0.35 mm 10...58 Hz
Shock resistance	30 gn 11 ms IEC 88 reference 2-27

Ordering and shipping details

Category	18215-ADVANTYS STB I/O
Discount Schedule	PC32
GTIN	3595863949223
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.02 in (2.600 cm)
Package 1 Width	3.15 in (8.000 cm)
Package 1 Length	5.16 in (13.100 cm)
Package 1 Weight	4.30 oz (122.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	42
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	12.03 lb(US) (5.458 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

