


STANDARD CABLE TIES




See
page A-25 for
mil-specs

Intermediate 30 lb., 40 lb. Natural, UV Black

| Per Bag | Part Number | Colour & Material | Length Inch/mm | Width Inch/mm | Thickness Inch/mm | Tie Tensile | Diameter Inch/mm | UR-CSA Mil-Spec | Per Case |
|---------|-------------|-------------------|----------------|---------------|-------------------|-------------|------------------|------------------|----------|
| 1,000 | L-5409M | Natural Nylon | 5.84/148.33 | .140/3.556 | .049/1.244 | 40 lb. | 1.437/36.512 | UR-CSA MS3367-S* | 10,000 |
| 100 | L-5409C | Nylon | | | | | | | |
| 1,000 | L-5400M | UV Black Nylon | 8.875/225.42 | .140/3.556 | .049/1.244 | 40 lb. | 2.375/60.325 | UR-CSA MS3367-S* | 10,000 |
| 100 | L-5400C | Nylon | | | | | | | |
| 1,000 | L-8409M | Natural Nylon | 8.875/225.42 | .140/3.556 | .049/1.244 | 40 lb. | 2.375/60.325 | UR-CSA MS3367-S* | 10,000 |
| 100 | L-8409C | Nylon | | | | | | | |
| 1,000 | L-8400M | UV Black Nylon | 11.56/293.67 | .140/3.556 | .058/1.473 | 40 lb. | 3.375/85.72 | UR | 5,000 |
| 100 | L-8400C | Nylon | | | | | | | |
| 100 | L-11409C | Natural Nylon | 11.56/293.67 | .140/3.556 | .058/1.473 | 40 lb. | 3.375/85.72 | UR | 5,000 |
| 100 | L-11400C | UV Black Nylon | | | | | | | |
| 100 | L-14409C | Natural Nylon | 14.50/368.30 | .140/3.556 | .058/1.473 | 40 lb. | 4.00/101.60 | UR | 5,000 |
| 100 | L-14400C | UV Black Nylon | | | | | | | |

Tolerance: .XXX = ±.005, .XX = ±.015, Fraction = ±1/32"



Standard 50 lb. Natural, UV Black

| Per Bag | Part Number | Colour & Material | Length Inch/mm | Width Inch/mm | Thickness Inch/mm | Tie Tensile | Diameter Inch/mm | UR-CSA Mil-Spec | Per Case |
|---------|-------------|-------------------|----------------|---------------|-------------------|-------------|------------------|------------------|----------|
| 1,000 | L-7509M | Natural Nylon | 7.56/192.07 | .180/4.572 | .052/1.320 | 50 lb. | 1.875/47.625 | UR-CSA MS3367-1* | 10,000 |
| 100 | L-7509C | Nylon | | | | | | | |
| 1,000 | L-7500M | UV Black Nylon | 11.25/285.75 | .180/4.572 | .052/1.320 | 50 lb. | 3.062/77.787 | UR-CSA MS3367-7* | 5,000 |
| 100 | L-7500C | Nylon | | | | | | | |
| 500 | L-11509D | Natural Nylon | 11.25/285.75 | .180/4.572 | .052/1.320 | 50 lb. | 3.062/77.787 | UR-CSA MS3367-7* | 5,000 |
| 100 | L-11509C | Nylon | | | | | | | |
| 500 | L-11500D | UV Black Nylon | 14.56/369.87 | .180/4.572 | .052/1.320 | 50 lb. | 4.125/104.775 | UR-CSA MS3367-2* | 5,000 |
| 100 | L-11500C | Nylon | | | | | | | |
| 500 | L-14509D | Natural Nylon | 14.56/369.87 | .180/4.572 | .052/1.320 | 50 lb. | 4.125/104.775 | UR-CSA MS3367-2* | 5,000 |
| 100 | L-14509C | Nylon | | | | | | | |
| 500 | L-14500D | UV Black Nylon | 17.09/434.16 | .187/4.749 | .060/1.524 | 50 lb. | 4.75/120.65 | UR | 5,000 |
| 100 | L-14500C | Nylon | | | | | | | |
| 100 | L-17509C | Natural Nylon | 17.09/434.16 | .187/4.749 | .060/1.524 | 50 lb. | 4.75/120.65 | UR | 5,000 |
| 100 | L-17500C | UV Black Nylon | | | | | | | |

Tolerance: .XXX = ±.005, .XX = ±.015, Fraction = ±1/32"

MADE IN  U.S.A.

