



Main

| | |
|-----------------------------|---|
| Product or Component Type | Circuit breaker |
| Range | PowerPact P |
| Current Sensor Rating Range | 1200 A |
| Rated Current | 1200 A |
| Breaking Capacity | 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC |
| AWG Gauge | AWG 3/0...500 kcmil aluminum/copper)4 |
| Trip Unit Technology | Electronic, ammeter, Micrologic 3.0 A, LI |

Complementary

| | |
|-----------------------------|---|
| Certifications | CSA UL listed IEC |
| Rated operational Voltage | 600 V AC |
| Module Type | P-Frame |
| Mounting Location | Bolt-on |
| Mounting Mode | Unit mount |
| Poles Description | 3P |
| Circuit Breaker Rating Code | J |
| Electrical Connection | Lugs load Lugs line |
| Continuous Current Rating | 100 % |
| Device Short Name | A |
| Height | 16.16 in (410.46 mm) |
| Depth | 8.05 in (204.47 mm) |
| Width | 8.27 in (210.06 mm) |
| Tightening Torque | 442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Packing Units

| | |
|------------------|--------------------------|
| Package 1 Weight | 32.00 lb(US) (14.515 kg) |
|------------------|--------------------------|

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|