

# Product data sheet

## Characteristics

# GS2AH420

External rotary handle, TeSys GS, red handle, front mounting, 2 positions I-O, NEMA 4-4X, for GS 30A Compact UL



### Main

Range of Product	TeSys
Range	TeSys
Device short name	GS2AH
Product or Component Type	Rotary handle
Range compatibility	TeSys TeSys GS GS1D fuse-switch disconnect
Type of operating handle	External frontal
Handle colour	Red
Handle front plate colour	Yellow

### Complementary

Handle positions	O-I
Rotary handle padlocking	With
Switch rated current	30 A
Standards	CSA UL
Net Weight	0.44 lb(US) (0.2 kg)

### Environment

NEMA Degree of Protection	NEMA 4/4X
---------------------------	-----------

### Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	3389119411868
Returnability	Yes
Country of origin	FR

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.44 in (6.2 cm)
Package 1 Width	2.95 in (7.5 cm)
Package 1 Length	4.72 in (12 cm)
Package 1 Weight	7.83 oz (222 g)
Unit Type of Package 2	S01
Number of Units in Package 2	3
Package 2 Height	5.91 in (15 cm)
Package 2 Width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	29.63 oz (840 g)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	18 months
----------	-----------