
BURNDY

KS23, Split Bolt Connector, Run/Tap: #6 AWG-#2 AWG Str

By Burndy
Catalog # KS23

Copper Split Bolt, Cu: 6 AWG-2 AWG (Str) (Run & Tap)



Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Application

For Direct Burial Applications In Earth Or Concrete, Copper

Specifications

Certification - UL Recognized	No
Certification - cULus	No
EU RoHS Indicator	Yes
Industry Standard(s)	RUS
Certification - ETL	No
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Copper Str Run Range	6 STR - 2 STR
Conductor - Copper Str Run	• 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG
Conductor - Copper Solid Run Range	6 AWG-1 AWG
Conductor - Copper Solid Run	1 AWG
Conductor - Copper Solid Tap Range	14 AWG-1 AWG
Conductor - Copper Solid Tap	1 AWG
Conductor - CopperWeld Solid Tap Range	#1
Conductor - CopperWeld Solid Tap	#1
Conductor - CopperWeld Solid Run Range	#1
Conductor - CopperWeld Solid Run	#1
Conductor - CopperWeld Str Tap Range	3 #7-5D
Conductor - CopperWeld Str Tap	• 3 #7 • 3A • 5D
Conductor - CopperWeld Str Run Range	3 #7-5D
Conductor - CopperWeld Str Run	• 3 #7 • 3A • 5D
Conductor Type	• CU C Solid-Run • CU C Str-Run • CU Weld C Solid-Run • CU Weld C Str-Run • CU C Str-Tap • CU Weld C Solid-Tap • CU Weld C Str-Tap • CU C Solid-Tap
Conductor - Copper Str Tap Range	6 STR - 2 STR
Conductor - Copper Str Tap	• 14 AWG • 12 AWG • 10 AWG • 8 AWG • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG

Configuration

Connector Type	Split Bolt

Dimensions

Package Height	0.000 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	39 mm
Width	0.62 in
Dimension - Width fraction	31/50 in

Dimension - B Length fraction	18/25 in
Dimension - Width mm	16 mm
Dimension - Width inch	0.62 in
Dimension - B Length inch	.72 in
Dimension - Cross Flats inch	0.82 in
Dimension - Length Overall inch	1.54

Sub Brand	SERVIT
UPC	781810012758
Type	KS, Compact
Material	Copper
Plating Type	Unplated
UPC 12 Digit	781810012758
UPC 14 Digit GTIN	00781810012758

Force Related

Installation Torque Recommended in-lb	275 in

Logistics

Pallet Quantity	44000
Carton Quantity	100

General

Trade Name	SERVIT®
Plated	N

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved