



Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Rail
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting Support	Fixing nut
Range compatibility	Spacial Spacial S3D Spacial Spacial CRN Spacial Spacial S3X Thalassa Thalassa PLM
Device composition	1 upright
Quantity per Set	Set of 10
Material	aluminium

Complementary

Fixing mode	Screwed M8 - on backstuds of enclosure
Height	Nominal 31.50 in (800 mm)
Width	0.98 in (25 mm)
Depth	0.59 in (15 mm)
Thickness	0.10 in (2.5 mm)
Net Weight	0.51 lb(US) (0.23 kg)

Ordering and shipping details

Category	80035-ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	3606480182969
Returnability	Yes
Country of origin	FR

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.40 in (3.556 cm)
Package 1 Width	1.00 in (2.54 cm)
Package 1 Length	29.25 in (74.295 cm)
Package 1 Weight	8.00 oz (226.799 g)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------