

# Installation and Assembly Products

## Powr-Fish® Pull Line



- Continuous-fiber polyline can be blown directly into conduit
- Can be left in conduit for future use
- Will not rot or mildew

Description	Cat. No.
6,500 ft. Length, 210 lb. min. Tensile Strength in Bucket w/ Prepunched Lid	31-340
3,250 ft. Length, 210 lb. min. Tensile Strength	31-341
10,000 ft. Length, 210 lb. min. Tensile Strength	31-342
6,500 ft. Length, 210 lb. min. Tensile Strength	31-343
2,200 ft. Length, 500 lb. min. Tensile Strength	31-344
1,500 ft. Length, 1,000 lb. min. Tensile Strength	31-345

## Yellow 77® Wire Pulling Lubricant

31-351



31-358

- Wax-based formula provides superior lubricity
- Safe to use with most cable types except low-density polyethylene and semi-conducting jackets
- Won't breakdown or separate after repeated exposure to freezing temperatures
- Dries to a thin, non-conductive film that won't clog conduit
- Clings to cable throughout long pulls
- Easy to apply by hand or with pump
- Creamy texture applies easily and uniformly
- Homogeneous blend requires no mixing
- Won't dry out – surface coat forms to control evaporation
- Environmentally safe – non-toxic, non-flammable and non-corrosive

Description	Cat. No.
15-oz. Aerosol	31-356
1-Qt. Squeeze Bottle	31-358
1-Qt. Tub	31-350
1-Gal. Bucket	31-351
5-Gal. Bucket	31-355
55-Gal. Drum	31-365

## Yellow 77® Plus Wire Pulling Lubricant

31-391



31-398

- Teflon® additive provides greater lubricity than other wax-based lubricants
- Safe to use with all cable types
- Remains stable in high temperatures – usable from 30°F to 190°F (-1°C to 88°C)
- Dries slowly to a thin, non-conducting film that won't harden in conduit
- Clings to cable throughout long runs
- Easy to apply by hand or with pump
- Creamy texture applies easily and uniformly
- Homogeneous blend requires no mixing
- Won't dry out – surface coat forms to control evaporation
- Environmentally safe – non-toxic, non-flammable and non-corrosive

Description	Cat. No.
1-Qt. Squeeze Bottle	31-398
1-Gal. Bucket	31-391
5-Gal. Bucket	31-395

## ClearGlide™ Wire Pulling Lubricant

31-381



31-388

- Clear and colorless for quick and easy clean-up
- Exceptional lubricity for super-fast pulls
- Polymer-based formula perfect for all electrical and datacom applications
- Safe to use with all cable types
- Remains stable over wide temperature range – usable from 30°F to 180°F (-1°C to 82°C)
- Dries to a semi-fluid film that won't clog conduit
- Clings to cable throughout long pulls
- Easy to apply by hand, brush or pump
- Environmentally safe – non-toxic, non-flammable and non-corrosive

Description	Cat. No.
1-Qt. Squeeze Bottle	31-388
1-Gal. Bucket	31-381
5-Gal. Bucket	31-385

Pull Line/Wire Pulling Lubricants