



GE
Lighting

74095 - GE432MAX347-N

GE LFL UltraMax™ Electronic High Efficiency Multivolt Instant Start Ballast

- Energy saving high efficiency instant start electronic ballast (> 90%)
- Instant start ballast for long lamp starting cycles and low initial cost
- Anti-Striation Control for better light quality, with no striations.
- Cold temperature -20F Minimum Starting Temperature
- Light-weight, Low Profile Housing
- Parallel lamp operation means system maintenance is easier to manage

GENERAL CHARACTERISTICS

Application	4 or 3- F32T8 347V "N" .87 BF UltraMax
Category	Linear Fluorescent
Ballast Type	Electronic - High Efficiency Multivolt Instant Start
Starting Method	Instant start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-) (NOM)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal Can
Additional Info	Anti-striation control / Auto-restart / Inherent thermal protection

PRODUCT INFORMATION

Product Code	74095
Description	GE432MAX347-N
Standard Package	Case
Standard Package GTIN	10043168740958
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168740951

DIMENSIONS

Case dimensions			
Length (L)		9.5 in(241.30 mm)	
Width (W)		1.3 in(33.02 mm)	
Height (H)		1.2 in(29.97 mm)	
Mounting dimensions			
Bracket Length (BL)		NaN in(NaN mm)	
Mount Length (M)		8.9 in(226.06 mm)	
Mount Width (X or F)		1.1 in(27.94 mm)	
Mount Slots (MS)		0.3 in(7.62 mm)	
Weight (NOM)		1.04 lb	
Exit Type		Side	
Remote Mounting Distance (NOM)		18.0 ft	
Remote Mounting Wire Gauge (NOM)		18.0 AWG	
Lead lengths	Qty	Exit	Length (± 1 in.)
Black	1	Left	25.0 (635 mm)
White	1	Left	25.0 (635 mm)
Blue	2	Right	31 in (NaN mm)
Red	2	Right	31.0 (787 mm)
Yellow	2	Right	47.0 (1194 mm)

SAFETY & PERFORMANCE

- CSA
- Meets ANSI Standard C82.11-Cons 2002
- Meets ANSI Standard C62.41-1991
- NEMA Premium®
- Meets ICES-005 for EMI and RFI
- Type 1 Outdoor
- Type HL
- Product is compliant with material restriction requirements of RoHS

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (°F/ °C)
FE15T8	3	347	38	0.11 A	0.82	2.16	97	1.5	17.0	-22.0 °F / NaN
FE15T8	4	347	46	0.14 A	0.80	1.74	98	1.5	15.0	-22.0 °F / NaN
F32T8/WM	3	347	83	0.24 A	0.92	1.11	99	1.5	6.0	60.0 °F / NaN

F32T8/WM	4	347	100	0.29 A	0.86	0.86	99	1.5	5.0	60.0 °F / NaN
F32T8/25W	4	347	84		0.84	1.00	99	1.6	5.0	60.0 °F / NaN
F32T8	3	347	87	0.25 A	0.94	1.08	99	1.6	5.0	-22.0 °F / NaN
F32T8	4	347	106	0.3 A	0.88	0.83	99	1.6	5.0	-22.0 °F / NaN
F28T8/UMX	3	347	77	0.22 A	0.90	1.17	99	1.5	6.0	60.0 °F / NaN
F28T8/UMX	4	347	93	0.27 A	0.84	0.90	99	1.6	5.0	60.0 °F / NaN
F25T8/WM	4	347	71		0.88	1.24	99	1.6	6.0	60.0 °F / NaN
F25T8	3	347	69	0.2 A	0.95	1.38	99	1.5	7.0	-22.0 °F / NaN
F25T8	4	347	83	0.24 A	0.88	1.06	99	1.6	6.0	-22.0 °F / NaN
F25T12	3	347	73	0.21 A	0.96	1.32	99	1.5	7.0	-22.0 °F / NaN
F25T12	4	347	88	0.25 A	0.88	1.00	99	1.6	6.0	-22.0 °F / NaN
F17T8/WM	4	347	50		0.83	1.66	99	1.6	10.0	60.0 °F / NaN
F17T8	3	347	48	0.14 A	0.90	1.88	98	1.5	12.0	-22.0 °F / NaN
F17T8	4	347	58	0.17 A	0.83	1.43	99	1.6	10.0	-22.0 °F / NaN

CAUTIONS & WARNINGS

NOTES

- For 3 lamp application, cap unused blue lead, insulate for 600 Vrms

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.