

LZ7H2X43BD

Ultra compact starter, TeSys Hybrid, Safe Torque Off, 3P, 500VAC, 0.75kW at 400V, 24VDC, Spring termina



Main

| | |
|-------------------------------------|--|
| Range | TeSys |
| Product name | TeSys Hybrid |
| Device short name | LZ7H |
| Product or Component Type | Ultra-compact starter |
| Motor starter type | Direct on line |
| Poles description | 3P |
| [Ue] rated operational voltage | 500 V AC |
| [Ie] rated operational current | 2.4 A 500 V AC-51 2.4 A 500 V AC-53A 2.4 A 500 V AC-51 mounting side by side 2.4 A 500 V AC-53A mounting side by side |
| Thermal protection adjustment range | 0.18...2.4 A |
| Motor power kW | 0.37 kW 220 V AC 0.65 0.37 kW 230 V AC 0.65 0.75 kW 380 V AC 0.65 0.75 kW 400 V AC 0.65 0.75 kW 415 V AC 0.65 0.75 kW 440 V AC 0.65 1.1 kW 500 V AC 0.65 |
| Maximum Horse Power Rating | 0.5 Hp 200 V AC 0.5 Hp 230 V AC 1 hp 460 V AC |
| [Uc] control circuit voltage | 24 V DC |
| Safety level | SIL 3 IEC 61508-1 stop function PL = e ISO 13849-1 stop function SIL 2 IEC 61508-1 motor protection |
| Safety reliability data | MTTFd = 517 years stop function SFF = 99 % stop function SFF = 99 % motor protection MTTFd = 447 years motor protection PFHd = 2.40E-9 1/h stop function |
| Thermal overload class | Class 10A IEC 60947-4-2 |

Complementary

| | |
|--------------------------------|---|
| Auxiliary contact composition | 1 C/O fault signalling |
| Control circuit voltage limits | 19.2...30 V DC |
| Current consumption | <= 40 mA 24 V DC |
| Reset | Manual Electrical reset |
| Electrical durability | 30 Mcycles |
| Maximum operating rate | 120 Cyc/Mn AC-51 50 % 6 cyc/mn AC-53A 50 % |
| Mounting Mode | By clips |
| Mounting Support | DIN rail |
| Connections - terminals | Spring clamp terminals 1 0.00...0.00 in ² (0.2...2.5 mm ²) rigid Spring clamp terminals 1 0.00...0.00 in ² (0.25...2.5 mm ²) flexible - with cable end Spring clamp terminals 1 0.00...0.00 in ² (0.2...2.5 mm ²) flexible - without cable end |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|--|---|
| Certifications | CE ATEX as associated device for motor protection in zones 1 and 21 CULus |
| Standards | UL 60947-4-1 IEC 60947-4-2 |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Pollution degree | 2 |
| Width | 0.89 in (22.5 mm) |
| Height | 3.90 in (99 mm) |
| Depth | 4.51 in (114.5 mm) |
| Net Weight | 7.48 oz (212 g) |

Environment

| | |
|---------------------------------------|---|
| IP degree of protection | IP20 |
| Protective treatment | TC |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) without derating |
| Ambient Air Temperature for Storage | -40...176 °F (-40...80 °C) |

Ordering and shipping details

| | |
|-------------------|---|
| Category | 22349-TESYS H ELECTRONIC STARTER 0-6.5A |
| Discount Schedule | I12 |
| GTIN | 3606485421025 |
| Returnability | No |
| Country of origin | DE |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.42 in (3.600 cm) |
| Package 1 Width | 4.61 in (11.700 cm) |
| Package 1 Length | 4.72 in (12.000 cm) |
| Package 1 Weight | 8.36 oz (237.0 g) |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 5.91 in (15.000 cm) |
| Package 2 Width | 5.91 in (15.000 cm) |
| Package 2 Length | 15.75 in (40.000 cm) |
| Package 2 Weight | 5.69 lb(US) (2.581 kg) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |