

Product data sheet

Specifications



Power distribution block, Linergy, 3 pole, 1 line, 6 load, 380A Cu, 600V

9080LBC363106

Product availability: Stock - Normally stocked in distribution facility

Main

Range	9080LB
Product	Power Distribution Block
Current Rating	380 A copper

Complementary

Voltage Rating	600 V AC/DC
Mounting Type	Surface mount
Number of poles	3
Terminals per Pole	1 line 6 load
Wire Size	Line 6, AWG 4...500 kcmil, copper Load 1, AWG 14...AWG 2, copper
Electrical Connection	Tin plated copper lugs
SCCR	100 kA UL 508 A
Ambient Air Temperature for Operation	-40...302 °F (-40...150 °C)
Block Material	Phenolic: block
Terminal Tightening Torque	Load lug 40 lbf.in (4.5 N.m) AWG 8 copper Load lug 35 lbf.in (4.0 N.m) AWG 14...AWG 10 copper Line lug 375 lbf.in (42.4 N.m) AWG 4...500 kcmil copper Load lug 50 lbf.in (5.6 N.m) AWG 2 copper Load lug 45 lbf.in (5.08 N.m) AWG 6...AWG 4 copper
Wire stripping length	Line: 1.06 in (26.92 mm) Load: 1 in (25.4 mm) for bottom connection Load: 1.56 in (39.62 mm) for top connection
Height	4 in (101.6 mm)
Width	5 in (127 mm)
Depth	2.61 in (66.29 mm)
End Barrier	9080LB33

Environment

Certifications	CSA file 70361 class 6228 01 UL recognized E60616 CCN XCFR2 CE
----------------	--

Ordering and shipping details

Category	US10CP121711
Discount Schedule	OCP1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	785901097686
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.900 in (7.366 cm)
Package 1 Width	4.50 in (11.43 cm)
Package 1 Length	5.200 in (13.208 cm)
Package weight(Lbs)	2.209 lb(US) (1.002 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	16
Package 2 Height	10.100 in (25.654 cm)
Package 2 Width	11.200 in (28.448 cm)
Package 2 Length	13.200 in (33.528 cm)
Package 2 Weight	39.789 lb(US) (18.048 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions

