



### Main

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessories
Product specific application	Light hoisting applications
Product compatibility	XKB
Accessory / separate part type	Potentiometer
Condition of use	For applications requiring an extended neutral zone
Ohmic value	4700 Ohm
Size	15 mm

### Complementary

Standards	UTE 93-265
Potentiometer characteristic	Linear function Continuous rotational operation
Operating angle	360 °
Mechanical durability	3000000 cycles
Centre tap	Wired out to terminal
Centre tap dead zone	40 °
Power dissipation in W	3 W 185 °F (85 °C)
Connections - terminals	Flying leads from soldered standard tags
Net weight	0.12 lb(US) (0.055 kg)

### Environment

Mounting mode	By the body
---------------	-------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.22 oz (63 g)
Package 1 Height	1.77 in (4.5 cm)
Package 1 width	2.28 in (5.8 cm)

---

Package 1 Length	2.48 in (6.3 cm)
------------------	------------------

---

### Offer Sustainability

---

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---