



Main

| | |
|-------------------------------|---|
| Range of product | OsiSense XU |
| Series name | Application |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XUY |
| Sensor design | Compact |
| Detection system | Polarised reflex |
| Material | Plastic |
| Line of sight type | Lateral |
| Type of output signal | Discrete |
| Supply circuit type | DC |
| Wiring technique | 4-wire |
| Discrete output type | PNP/NPN |
| Discrete output function | 1 NO or 1 NC programmable |
| Electrical connection | 1 male connector M8, 4 pins |
| Product specific application | Position or presence control of parts on conditioning machine Detection of shiny parts Through beam on a conveyor |
| Emission | Red LED |
| [Sn] nominal sensing distance | 0.07...3.28 ft (0.02...1 m) with reflector Ø 46 mm 0.07...6.56 ft (0.02...2 m) with reflector Ø 84 mm |

Complementary

| | |
|---------------------------|---|
| Enclosure material | Polycarbonate strong housing |
| Pulse frequency | 8 kHz |
| Output type | Solid state |
| [Us] rated supply voltage | 12...24 V DC reverse polarity protection |
| Supply voltage limits | 10...30 V DC |
| Switching capacity in mA | 100 mA overload and short-circuit protection) |
| Switching frequency | <= 1 kHz |
| Maximum voltage drop | <2 V 100 mA closed state) <1 V 10 mA closed state) |

| | |
|------------------------|-------------------------|
| Current consumption | < 40 mA no-load |
| Maximum delay response | 500 ms |
| Maximum delay recovery | 500 ms |
| Setting-up | Parametering by buttons |
| Depth | 0.51 in (13 mm) |
| Length | 3.07 in (78 mm) |
| Width | 1.18 in (30 mm) |

Environment

| | |
|---------------------------------------|--|
| Product certifications | CE CULus |
| Ambient air temperature for operation | 32...140 °F (0...60 °C) |
| Ambient air temperature for storage | -4...176 °F (-20...80 °C) |
| Immunity to ambient light | 10000 lux incandescent bulb 20000 lux natural light |
| IP degree of protection | IP65 IEC 60529 |

Packing Units

| | |
|------------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 1.80 oz (51 g) |
| Package 1 Height | 1.38 in (3.5 cm) |
| Package 1 width | 2.76 in (7 cm) |
| Package 1 Length | 5.12 in (13 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|