



Main

Product	End tap box
Range	I-Line

Complementary

Rated Current	800 A copper
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	29.14 in (740.16 mm)
Height	28 in (711.20 mm)
Width	11 in (279.40 mm)
Material	Copper: busbar
I-LINE Value End	Bolt
Number of Phases	3 phase
For Use with	Busbar trunking 800 A copper
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire

Environment

Standards	IEC 61439-2 UL 857 CSA C22.2 No 27:1994
-----------	---

Ordering and shipping details

Category	20029-800A CU FEEDER BUS IP54 THERMAL
Discount Schedule	PE8
GTIN	785901022763
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.13 in (74.0 cm)
Package 1 Width	10.98 in (27.9 cm)
Package 1 Length	27.99 in (71.1 cm)
Package 1 Weight	153.00 lb(US) (69.4 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------