

Product data sheet

Characteristics

8910DPA43V09

Contacteur, Definite Purpose, 40A, 3 pole,
25HP at 575VAC, 3 phase, 208/240VAC 60Hz
220VAC 50Hz coil, open



Main

| | |
|---------------------------|----------------------------|
| Product or Component Type | Definite Purpose Contactor |
| Line Rated Current | 40 A |
| Number of Poles | 3P |
| Pole contact composition | 3 NO |
| Range of Product | DPA |

Complementary

| | |
|--------------------------------|---|
| Maximum Horse Power Rating | 3 Hp 115 V AC, 1 phase 7.5 Hp 230 V AC, 1 phase 10 Hp 230 V AC, 3 phase 20 Hp 460 V AC, 3 phase 25 hp 575 V AC, 3 phase |
| Locked rotor rated current | 240 A 277 V AC 200 A 460 V AC 160 A 575 V AC |
| [Ue] rated operational voltage | 600 V AC |
| [Uc] control circuit voltage | 208...240 V AC 60 Hz 220 V AC 50 Hz |
| Phase | 3 phase |
| Electrical Connection | Quick connect terminals Box lugs |

Environment

| | |
|------------------------|--------------------------|
| Product Certifications | UL Recognized[RETURN]CSA |
|------------------------|--------------------------|

Ordering and shipping details

| | |
|-------------------|---------------------------|
| Category | 21344-8910 DPA 4_(40 AMP) |
| Discount Schedule | CP1B |
| GTIN | 785901073437 |
| Returnability | Yes |
| Country of origin | CN |

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.40 in (6.096 cm) |
| Package 1 Width | 3.90 in (9.906 cm) |
| Package 1 Length | 3.10 in (7.874 cm) |
| Package 1 Weight | 16.00 oz (453.592 g) |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|