



## Main

|                       |                                      |
|-----------------------|--------------------------------------|
| Product               | Miniature circuit-breaker            |
| Range                 | QO                                   |
| Current Rating        | 20 A                                 |
| Voltage Rating        | 120/240 V AC<br>240 V AC<br>120 V AC |
| Mounting Type         | Plug-in                              |
| Number of Poles       | 3P                                   |
| Circuit Breaker Type  | Standard                             |
| Ratings               | HACR rated                           |
| Electrical Connection | Pressure plate                       |

## Complementary

|                        |   |
|------------------------|---|
| Interrupt Rating       | 10 KA 120/240 V AC 50/60 Hz<br>10 KA 240 V AC 50/60 Hz<br>10 kA 120 V AC 50/60 Hz |
| Number of Panel Spaces | 3   |
| Wire Size              | AWG 14...AWG 8 copper or aluminium  |
| Tightening Torque      | 35.40 lbf.in (4 N.m)  |
| Height                 | 2.99 in (76 mm)   |
| Width                  | 2.24 in (57 mm)   |
| Depth                  | 2.91 in (74 mm)   |
| Net Weight             | 0.85 lb(US) (0.386 kg)  |

## Environment

|                |                      |
|----------------|----------------------|
| Certifications | UL Listed[RETURN]CSA |
| Ambient Rating | 104 °F (40 °C)       |

## Ordering and shipping details

|                   |                                 |
|-------------------|---------------------------------|
| Category          | 00012-QO 3 POLE CIRCUIT BREAKER |
| Discount Schedule | DE2A                            |
| GTIN              | 785901400684                    |
| Returnability     | Yes                             |
| Country of origin | MX                              |

## Packing Units

|                              |                    |
|------------------------------|--------------------|
| Unit Type of Package 1       | PCE                |
| Number of Units in Package 1 | 1                  |
| Package 1 Height             | 2.60 in (6.604 cm) |
| Package 1 Width              | 2.20 in (5.588 cm) |
| Package 1 Length             | 3.00 in (7.62 cm)  |
| Package 1 Weight             | 13.62 oz (386.0 g) |
| Unit Type of Package 2       | BB1                |
| Number of Units in Package 2 | 3                  |
| Package 2 Height             | 3.80 in (9.652 cm) |
| Package 2 Width              | 2.20 in (5.588 cm) |

|                              |                        |
|------------------------------|------------------------|
| Package 2 Length             | 7.20 in (18.288 cm)    |
| Package 2 Weight             | 2.50 lb(US) (1.134 kg) |
| Unit Type of Package 3       | CAR                    |
| Number of Units in Package 3 | 36                     |
| Package 3 Height             | 3.80 in (9.652 cm)     |
| Package 3 Width              | 14.40 in (36.576 cm)   |
| Package 3 Length             | 21.60 in (54.864 cm)   |
| Package 3 Weight             | 3.06 lb(US) (1.388 kg) |

### Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product                    |
| REACH Regulation            | <a href="#">REACH Declaration</a>        |
| EU RoHS Directive           | Compliant with Exemptions                |
| Toxic heavy metal free      | Yes                                      |
| Mercury free                | Yes                                      |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information  | <a href="#">Yes</a>                      |
| Circularity Profile         | No need of specific recycling operations |
| Halogen content performance | Halogen free product                     |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|