



### Main

Range	TeSys
Device short name	GV3A
Product or component type	Auxiliary contact block
Product compatibility	GV3ME
Range compatibility	GV3 GV3ME circuit breaker
Mounting location	Front side
Auxiliary contacts operation	Fault signal 1 NC
Pole contact composition	1 NC
Quantity per set	Set of 10

### Complementary

[Ui] rated insulation voltage	600 V UL 508 690 V conforming to IEC 60947-1 600 V CSA C22.2 No 14
[Ue] rated operational voltage	48...690 V AC 24...220 V DC
[Ith] conventional free air thermal current	6 A
Protection type	GB2CB... circuit breaker GG fuse 6 A
Mechanical durability	1000 cycles
Rated operational power in VA	240 VA 48 V AC-11 1000 cycles 5 A 450 VA 440 V AC-11 1000 cycles 1 A 450 VA 500 V AC-11 1000 cycles 1 A 200 VA 690 V AC-11 1000 cycles 0.3 A 460 VA 110...127 V AC-11 1000 cycles 3.6 A 800 VA 220...240 V AC-11 1000 cycles 3.5 A 850 VA 380...415 V AC-11 1000 cycles 2.2 A
Rated operational power in W	180 W 24 V DC-11 1000 cycles 180 W 48 V DC-11 1000 cycles 135 W 60 V DC-11 1000 cycles 105 W 110 V DC-11 1000 cycles 90 W 220 V DC-11 1000 cycles
Maximum Width	0.35 in (9 mm)

### Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

### Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	00785901258063
Nbr. of units in pkg.	1
Package weight(Lbs)	0.05 lb(US) (0.02 kg)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.30 in (3.3 cm)
Package 1 width	2.68 in (6.8 cm)
Package 1 Length	2.95 in (7.5 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	60
Package 2 Weight	4.07 lb(US) (1.845 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------