

# Product Datasheet

## Characteristic

# XZCP0941L10

pre-wired connectors XZ - straight  
female - M8 - 4 pins - cable PUR 10m



## Main

accessory / separate part category	cabling accessory
accessory / separate part type	pre-wired connectors
series name	general purpose

## Complementary

electrical connection	M8, 4 pins straight female connector
cable connector fixing	screw-on
collar material	metal
status LED	without
cable length	32.81 ft (10 m)
cable outer diameter	0.2 in (5.2 mm)
cable composition	4 x 0.34 mm <sup>2</sup>
wire insulation material	PUR
System Voltage	60 V AC 75 V DC
Line Rated Current	4 A
contact resistance	5000 µOhm
insulating resistance	1 GΩ
product weight	0.79 lb(US) (0.36 kg)

## Environment

IP degree of protection	IP65 IP67 IP69K
product certifications	cULus
ambient air temperature for operation	-40...176 °F (-40...80 °C) (static) 23...176 °F (-5...80 °C) (flexing)
ambient air temperature for storage	-40...176 °F (-40...80 °C)

## Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available