

HC22R Series

200 AMP MAINS - 200 AMP / POSITION c/w Blank Compartment



METER
SOCKETS

CATALOGUE #	DESCRIPTION	METER POSITIONS	ENCLOSURE SIZE A X B X C	WEIGHT
HC22R	2 gang, 200 Amp main, 200 per position	2	15 ¹ / ₈ " x 5 ³ / ₈ " x 26 ¹ / ₂ "	42 lbs.
HC23R	3 gang, 200 Amp main, 200 per position	3	15 ¹ / ₈ " x 5 ³ / ₈ " x 35 ¹ / ₄ "	58 lbs.
HC24R	4 gang, 200 Amp main, 200 per position	4	15 ¹ / ₈ " x 5 ³ / ₈ " x 44"	74 lbs.

- Blank compartment on left side for underground
- Factory Bussed - 200 Amp Mains
- 4 Jaw meter socket
- 200 Amp - 600 Volts per position
- CSA enclosure 3
- Approved conductor range:
Line 6-250 MCM AWG CU/AL
Load No. 6-250 MCM AWG
- Combination OH/UG
- Used primarily in Cambridge, Ontario

- Order "SXC" hubs separate
- Approved for overhead or underground use
- Use SXC503 for 5th jaw at 9 O'clock

KNOCKOUT CODE	CONDUIT SIZE
G	1 ¹ / ₄ ", 1 ¹ / ₂ ", 2", 2 ¹ / ₂ "
AA	1 ¹ / ₂ "
F	1 ¹ / ₄ ", 1 ¹ / ₂ ", 2", 2 ¹ / ₂ ", 3"

