



Main

Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Female connector straight 4 pins M12
Collar material	Metal
Status LED	Without

Complementary

Cable connector fixing	Screw-on
Enclosure material	Plastic
Cable connection	Screw terminal $\leq 0,75 \text{ mm}^2$ 3...6 mm Pg 7
[Ue] rated operational voltage	125 V AC 150 V DC
[In] rated current	3 A
Insulating resistance	$> 1000 \text{ GOhm}$
Contact resistance	$\leq 8000 \text{ }\mu\text{Ohm}$
Product weight	0,02 kg

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-40...85 °C
RoHS EUR conformity date	0726
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.