

Product data sheet

Characteristics

VW3S8201R30

cable for pulse/direction signal, Lexium SD3, 5V, shielded, 3m



Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and external impulsion generator
Range Compatibility	Lexium SD3
Type of Cable	Shielded cable
Cable length	9.84 ft (3 m)

Complementary

Product Compatibility	SD326
[Uc] control circuit voltage	5 V
Electrical connection	1 connector 24-pole Molex SD326) Cable end open external impulsion generator)

Ordering and shipping details

Category	18286-STEPPER ACCESSORIES
Discount Schedule	PC55
GTIN	3389119224581
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2 cm)
Package 1 Width	10.24 in (26 cm)
Package 1 Length	11.02 in (28 cm)
Package 1 Weight	9.24 oz (262 g)
Unit Type of Package 2	S04
Number of Units in Package 2	30
Package 2 Height	11.81 in (30 cm)
Package 2 Width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Package 2 Weight	21.48 lb(US) (9.742 kg)
Unit Type of Package 3	S04
Number of Units in Package 3	30
Package 3 Height	11.81 in (30 cm)
Package 3 Width	15.75 in (40 cm)
Package 3 Length	23.62 in (60 cm)
Package 3 Weight	21.48 lb(US) (9.742 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------