

Product Datasheet

Characteristic

LA26400AB

FA/LA MOLDED CASE CIRCUIT
BREAKER, 600V, 400A, 2P, 1PH



Main

product or component type	Circuit breaker
range of product	I-Line
trip unit technology	Thermal-magnetic
breaking capacity code	A

Complementary

Line Rated Current	400 A
poles description	2P
breaking capacity	42 kA 120 V AC 42 kA 240 V AC 30 kA 480Y/277 V AC 10 kA 250 V DC
[Ue] rated operational voltage	600 V AC 125 V DC 250 V DC
mounting mode	I-Line
electrical connection	Lugs load I-Line connection line
AWG gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
terminal identifier	AL400LA
magnetic hold current	2000 A
magnetic tripping current	4000 A
wiring configuration	2-wire
phase connection	AB
Maximum Height	11 in (279.40 mm)
width	6 in (152.40 mm)
depth	5.84 in (148.34 mm)

Environment

product certifications	UL Listed CSA
------------------------	------------------

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	ENVPEP1410004EN
PVC free	Yes
Halogen content performance	Halogen free plastic parts product