


TYPE ILSCONS

Features

- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Vinyl insulation
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-18 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Ensures reliability for copper conductor



Catalog Number	Wire Range	Stud Size	Dimensions		Maximum Wire Insulated Diameter
			L	W	
44200-B10 *	18-22	4	.74	.22	.145
44201-B10 *	18-22	6	.91	.31	.145
44202-B10 *	18-22	8	.91	.31	.145
44203-B10 *	18-22	10	.91	.31	.145
44204-B10 *	18-22	1/4	1.10	.46	.145
44205-B10 *	18-22	5/16	1.14	.53	.145
44206-B10 *	18-22	3/8	1.14	.53	.145
44210-B10 *	14-16	4	.80	.25	.175
44211-B10 *	14-16	6	.88	.25	.175
44212-B10 *	14-16	8	.94	.31	.175
44213-B10 *	14-16	10	.94	.31	.175
44214-B10 *	14-16	1/4	1.06	.53	.175
44215-B10 *	14-16	5/16	1.06	.53	.175
44216-B10 *	14-16	3/8	1.06	.53	.175
44220-B10 *	10-12	6	.95	.28	.255
44221-B10 *	10-12	8	.95	.28	.255
44222-B10 *	10-12	10	1.00	.38	.255
44223-B10 *	10-12	1/4	1.22	.53	.255
44224-B10 *	10-12	3/8	1.33	.53	.255
44225-B10 *	10-12	7/16	1.46	.71	.255

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Can be supplied in bulk. Consult factory for part number.

UL File E158587

- ✱ B5 = Bag of 5
- B10 = Bag of 10
- B100 = Bag of 100
- B1000 = Bag of 1000


TYPE ILSCONS

Features

- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Vinyl insulation
- UL Listed and CSA Certified for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-18 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Ensures reliability for copper conductor



A1

Catalog Number	Wire Range	Stud Size	Dimensions		Maximum Wire Insulated Diameter
			L	W	
44226-B10 *	10-12	1/2	1.52	.75	.255
44230-B5 *	8	10	1.28	.47	.385
44231-B5 *	8	1/4	1.28	.47	.385
44240-B5 *	6	10	1.62	.47	.440
44241-B5 *	6	1/4	1.62	.47	.440
44242-B5 *	6	5/16	1.70	.63	.440
44243-B5 *	6	3/8	1.70	.63	.440
44250-B5 *	4	10	1.81	.66	.515
44251-B5 *	4	1/4	1.81	.66	.515
44252-B5 *	4	5/16	1.81	.66	.515
44253-B5 *	4	3/8	1.81	.66	.515
44254-B5 *	4	7/16	1.81	.66	.515
44255-B5 *	4	1/2	2.41	.88	.515
45314-P100 *	14-16	10	.94	.31	.175
45315-P100 *	14-16	1/4	1.06	.53	.175
45316-P100 *	14-16	5/16	1.06	.53	.175
45316N-P100*	14-16	5/16	1.06	.53	.175
45317-P100 *	14-16	3/8	1.06	.53	.175
45414-P50 *	10-12	10	1.00	.38	.255
45415-P50 *	10-12	1/4	1.22	.53	.255
45416-P50 *	10-12	5/16	1.46	.71	.255
45417-P50 *	10-12	3/8	1.33	.53	.255

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

- * B5 = Bag of 5 P5 = Bag of 5
- B10 = Bag of 10 P10 = Bag of 10
- B100 = Bag of 100 P100 = Bag of 100
- B1000 = Bag of 1000 P1000 = Bag of 1000