

TM5SDM8DTS

Discrete I/O module, Modicon TM5, Digital input/output 4DI/4DO 24 V dc
Time stamp 1 wire



Main

Range of Product	Modicon TM5
Product or Component Type	Discrete I/O module
Discrete input number	4
Discrete input voltage	24 V
Discrete output number	4
Discrete output type	Transistor

Complementary

Range Compatibility	PacDrive LMC motion controller
Product Compatibility	PacDrive LMC Pro 2 PacDrive LMC Pro PacDrive LMC Eco
Discrete input voltage type	DC
Input voltage limits	20.4...28.8 V
Discrete input logic	Sink
Discrete input current	1.3 mA
Input impedance	18.4 kOhm
Output voltage	24 V DC
Output voltage limits	20.4...28.8 V
Discrete output logic	Source
Current per channel	0.1 A
Maximum current per output common	0.4 A
Color	White
Peak output current	0.4 A
Switching frequency	<= 16 kHz resistive
Input filtering	>= 2 µs hardware
Response time	<= 2 µs from state 0 to state 1 output <= 2 µs from state 1 to state 0 output
Maximum leakage current	25 µA when switched off
Protection Type	Overload protection Short-circuit protection Inductive overvoltage
Isolation	No insulation between channels 500 Vrms AC insulation between channel and bus
Maximum voltage drop	<0.9 V at 0.1 A output
Maximum supply current for sensors	600 mA
Current consumption	2 mA 5 V DC bus 62.5 mA 24 V DC input/output
Maximum power dissipation in W	1.51 W
Local signalling	1 LED green power supply 1 LED red power supply 8 LEDs input/output status
Electrical connection	1 wire
Net Weight	0.06 lb(US) (0.025 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	UL 508 CSA C22.2 No 142 IEC 61131-2
Product Certifications	EAC[RETURN]cULus[RETURN]CE[RETURN]C-tick
Ambient air temperature for operation	14...140 °F (-10...60 °C) with derating factor horizontal installation) 14...122 °F (-10...50 °C) with derating factor vertical installation)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Relative Humidity	5...95 % without condensation
IP degree of protection	IP20IEC 60529
Pollution degree	2 IEC 61131-2
Operating altitude	0...6561.68 ft (0...2000 m)
Storage altitude	0.00...9842.52 ft (0...3000 m)
Vibration resistance	1 gn 8.4...150 Hz DIN rail 3.5 mm 5...8.4 Hz DIN rail
Shock resistance	15 gn 11 ms
Electromagnetic compatibility	Electrostatic discharge immunity test, 4 kV on contact IEC 61000-4-2 Electrostatic discharge immunity test, 8 kV in air IEC 61000-4-2 Susceptibility to electromagnetic fields, 10 V/m 80...2000 MHz IEC 61000-4-3 Electrical fast transient/burst immunity test, 1 kV I/O IEC 61000-4-4 Electrical fast transient/burst immunity test, 1 kV shielded cable IEC 61000-4-4 Electrical fast transient/burst immunity test, 2 kV power lines IEC 61000-4-4 1.2/50 µs shock waves immunity test, 0.5 kV differential mode IEC 61000-4-5 1.2/50 µs shock waves immunity test, 1 kV common mode IEC 61000-4-5 Conducted RF disturbances IEC 61000-4-6 Conducted and radiated emissions CISPR 11

Ordering and shipping details

Category	22532-M258 PLC
Discount Schedule	PC12
GTIN	3606480908316
Returnability	No
Country of origin	AT

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.36 in (6.000 cm)
Package 1 Width	0.79 in (2.000 cm)
Package 1 Length	4.33 in (11.000 cm)
Package 1 Weight	1.38 oz (39.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	42
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	4.07 lb(US) (1.844 kg)