


YGHHC29C26 Compression Grounding C-TAP Connector

By Burndy
Catalog # [YGHHC29C26](#)



Compression ground connector, Material: Copper, Range Run: 3/0 Str-250 Kcmil, Tap: #6 sol-2/0 Str.

Features

- Double Figure C Connector, C-Shaped opening permits two continuous parallel cables into conductor groove
- Qualified to IEEE-837 2014
- Prefilled with PENETROX compound and strip sealed

Application

For Direct Burial cables

General

Catalog Number	YGHHC29C26
Connector Type	Tap
Die Index	997
EU RoHS Indicator	Contact Manufacturer
Material	Copper
Plated	N
Sub Brand	HYTAP
Trade Name	HYTAP™
Type	Taps
UPC	621945456235
UPC 12 Digit	6219454562355

Dimensions

Dimension - Height mm	0 mm
-----------------------	------

Conductor Related

Conductor - Copper Solid Tap Range	6 Solid - 2/0 Solid
Conductor - Copper Str Run Range	3/0 Stranded - 250 kcmil

Conductor - Copper Str Tap Range	6 Stranded - 2/0 Stranded
Conductor - Rod Run Range	1/2" or 5/8" Rod

Certifications And Compliance

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	[Delete]
Certification - UL Listed Direct Burial	Yes
Certified Listed	TAA Compliant (All status valid till December 2024)
Industry Standard(s)	<ul style="list-style-type: none"> • UL 467 • IEEE 837 • IEEE 837 2014 Qualified • UL 486A-486B
Standards - Industry Standards Met	UL467;IEEE 837;IEEE 837 2014 Qualified;UL 486A-486B
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	15
Minimum Pack Quantity	1
Pallet Quantity	3600

Product Assets

- [Catalogs - BURNDY Master Catalog - Section E1 - Compression Grounding](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Sales Drawings - 50064429](#)
- [Specifications - YGHHC29C26](#)