



### Main

Range of product	Lexium P, T
Product or component type	Delta 3 robot
Device short name	P4
Design	Standard

### Complementary

Number of axis	3...4
Operating position	Rotational 360°
Work envelope	0.00...47.24 in (0...1200 mm) diameter 0.00...16.73 in (0...425 mm) vertical
Repeat accuracy	0.1 mm
Permanent permissible load	33.07 lb(US) (15 kg)
Maximum actuation speed	32.81 ft/s (10 m/s)
Maximum acceleration	328.08 ft/s <sup>2</sup> (100 m/s <sup>2</sup> ) at 1 kg 246.06 ft/s <sup>2</sup> (75 m/s <sup>2</sup> ) at 1.5 kg
Net weight	264.55 lb(US) (120 kg)
Range compatibility	Lexium SH3 motor

### Environment

Environmental characteristic	Normal environment High pressure cleaner Dust pollution resistance
------------------------------	--

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	302.03 lb(US) (137 kg)

Package 1 Height	33.46 in (85 cm)
Package 1 width	3.94 in (10 cm)
Package 1 Length	47.24 in (120 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
PVC free	Yes