

Product data sheet

Specifications



Push-button, Harmony 9001K,
metal, flush, black, 30mm, spring
return, screw terminals for lug, 1NO

9001KR1BH5Y238

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony 9001K
Product or Component Type	Push-button

Complementary

Bezel material	Chromium plated metal
Mounting diameter	1.2 in (30 mm)
Contacts type and composition	1 NO
Device presentation	Complete product
Cap/operator or lens colour	Black
Type of operator	Spring return

Environment

IP Degree of Protection	IP65/IP66
-------------------------	-----------

Ordering and shipping details

Category	US10CS121426
Discount Schedule	0CS1
GTIN	785901169635
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.8 in (4.6 cm)
Package 1 Width	2.3 in (5.8 cm)
Package 1 Length	3.6 in (9.1 cm)
Package weight(Lbs)	4.3 oz (122.5 g)

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.7 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	49
Circularity Profile	End of Life Information
Take-back	No

Offer Marketing Illustration

Product benefits / Features

Features

Harmony 9001K



Improved security thanks to finger-safe contact blocks and light modules



Single screw Contact Block Fastening



Robustness to withstand the harshest environments



Automatic self-grounding operators without additional wiring



Large metal set of accessories to customize your product



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony 9001K

Compliant with IEC, UL, CSA, EN and NOM standards, CE marking

-25°C to +70°C operating temperature range

Contacts and heads designed against vibration (2 to 500 Hz: 7gn), ensuring secure mounting and wiring

Class I Div. 1 (gas) and Class II Div. 1 (dust) with reed contact blocks

American Bureau of Shipping Approved for Marine Applications & meet all US automotive standards

IP66, NEMA 4 rated (Heavy duty, oil tight, waterproof and dust tight without requiring boots)



4

Schneider

Electric

Jul 4, 2026