

Product data sheet

Characteristics

PS3620G

Plug-in unit, I-Line Busway, fusible, 200A, 600VAC, 3 pole, 3 fuse + G, plug in connection, vertical riser only



Main

Range of Product	I-Line
Product or Component Type	Plug-in unit

Complementary

[Ue] rated operational voltage	600 V AC
[Ie] rated operational current	200 A
Number of poles	3
Busbar description	Ground
Installation direction	Vertical
Fuse type	H, K, J or R
Disconnecter device type	Fusible disconnect

Environment

Product Certifications	CSA[RETURN]UL
------------------------	---------------

Ordering and shipping details

Category	20178-PQ/PS 200A FUSIBLE PLUGS
Discount Schedule	PE7
GTIN	785901012092
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------