

# RW90 Copper INSTAGLIDE®

600(61) RW90 CU BLK 600V

## Contact

Inside Sales Representatives  
Phone: 905-944-4300  
buildingwire.canada@nexans.com

**Nexans Ref.:** 12001114

**Country Ref.:** 643999

**EAN 13:** 622089107472

(-40°C) EXELENE® XLPE Insulated Wire 90°C Service Entrance and Branch Circuit Wire

## DESCRIPTION

CSA File #LL23462 Class 5832 03

Single compressed stranded copper with low temperature moisture resisting EXELENE® cross-linked polyethylene (XLPE) insulation. RoHS compliant.

Nexans INSTAGLIDE® reduced friction construction in copper sizes 6 AWG and larger, black and colours.

Colours: Standard colours are available.

Suitable flame retardant jacketed cables are available on request.

## Application

- For open wiring and raceways (except cabletroughs and ventilated flexible cableway) in dry or wet locations.
- For exposed wiring where exposed to weather with sunlight resistant insulation. Black and colours 6 AWG and larger are sunlight resistant and marked "SR".
- Non-jacketed RW90 (XLPE) cables are not suitable for installation in vaults and switchrooms under the conditions of CE Code Part 1 Rule 12-2202(3).
- Minimum recommended installation temperature minus 40°C (with suitable handling procedures).
- Maximum conductor temperature 90°C.
- Approved for use with ceiling fixtures.

## CHARACTERISTICS

### Construction characteristics


Conductor material	Copper
Insulation	XLPE
Jacket Colour	Black
With Bonding Conductor	No

### Dimensional characteristics

Approximate net weight	2930.36 kg/km
Cable Diameter	25.6 mm
Conductor size (AWG)	600 MCM
Number of cores	1
Number of strands	61

### Electrical characteristics

Maximum operating voltage	600 V
---------------------------	-------



## STANDARDS

**National** CSA C22.2 N° 38

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 2024-06-12 [www.nexans.ca](http://www.nexans.ca) Page 1 / 2

 Nexans

# RW90 Copper INSTAGLIDE®

600(61) RW90 CU BLK 600V

## Contact

Inside Sales Representatives  
Phone: 905-944-4300  
buildingwire.canada@nexans.com

### Usage characteristics

Maximum operating temperature	90 °C
Minimum installation temperature	-40 °C