



Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate without filter or grille: 44910.05 Gal/hr(US) (170 m3/h) Free flow rate with standard filter: 17171.49 Gal/hr(US) (65 m3/h) at 50 Hz
Input voltage	115 V 50/60 Hz

Complementary

Height	External 4.88 in (124 mm)
Width	External 4.88 in (124 mm)
Depth	External 2.17 in (55 mm)
Cut-out dimensions	Ø 108 mm
Material	Outlet grille ABS (acrylonitrile butadiene-styrene) Filter polyurethane foam
Color	Outlet grille Black Filter Black
IP degree of protection	IP20
Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480151385
Returnability	No
Country of origin	BG

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.44 in (6.2 cm)
Package 1 Width	6.50 in (16.5 cm)
Package 1 Length	5.83 in (14.8 cm)
Package 1 Weight	26.91 oz (763 g)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------