



## Main

Product or Component Type	Single Throw Safety Switch
Series name	General duty

## Complementary

Device Composition	Neutral (factory installed)
Disconnecter device type	Fusible disconnect
Short-circuit current	100 kA maximum cartridge
Device mounting	Surface
Number of poles	2
Electrical Connection	Lugs
[Ue] rated operational voltage	120/240 V AC
AWG gauge	AWG 1/0...750 kcmil copper or aluminium
Tightening torque	340 lbf.in (38.41 N.m) (AWG 1/0...250 kcmil)
Height	30.63 in (778.00 mm)
Width	22.25 in (565.15 mm)
Depth	10.13 in (257.30 mm)

## Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 3R galvanized steel

## Ordering and shipping details

Category	00008-H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	785901204756
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.79 in (27.4 cm)
Package 1 Width	22.80 in (57.9 cm)
Package 1 Length	31.42 in (79.8 cm)
Package 1 Weight	66.01 lb(US) (29.94 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------